

## Pneumatic Tacker Type 90/40-711

The BeA 90/40-711 is a well balanced tool, that operates quietly and efficiently while driving narrow crown staples type 90 from 15 to 40mm. The compact design allows the tool to be used even in hard to reach areas. The narrow nose of the 90/40-711 tool affords better operator visibility for more precise fastener placement.



### Popular applications:

Cabinetry, interior trim / finish work, millwork, casegoods, underlayment.

Length: 221 mm  
Width: 70 mm  
Height: 228 mm

### Technical data

Type description:	<b>90/40-711</b> Contact
Article code:	12000234
Magazine type :	Top loader
Safety:	Contact actuation
Fastener type:	Type 90
Magazine capacity:	125
Fasteners per strip:	1 x 100
Operating pressure:	5 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	0,9 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 82 dB
Single-shot sound pressure level:	L WA, 1 s,d= 91 dB
Weight:	1.34 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 3,3m/s<sup>2</sup>

**Extras supplied with the nailer:** Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

### Accessories:

Articel code	Description
14406200	Single actuation set
14403421	Remote valve
14403536	Mounting flange

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive  
for Machinery (89/392 EWG)

## Pneumatic Tacker Type 90/40-711

Staples type 90



BeA Deutschland  
Befestigungstechnik GmbH  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)



Description	L = Length mm
90/15 NK HZ	15
90/18 NK HZ	18
90/21 NK HZ	21
90/25 NK HZ	25
90/30 NK HZ	30
90/32 NK HZ	32
90/35 NK HZ	35
90/38 NK HZ	38
90/40 NK HZ	40

Other lengths and finishes are also available on request.

**Explanations:**

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut