

Pneumatic Tacker

Type 95/16-425

This compact and durable stapler is designed to perform well in heavy use industrial applications. The bottom loading magazine holds up to 114 staples and affords fast reloading and easy jam clearance. The 95/16-425 stapler drives 95 type staples in length from 6 to 16 mm. Comfortable rubber handle grip contributes to reduced operator fatigue. Rear exhaust is operator friendly and prevent lubrication from getting on materials being fastened.



Popular applications:

Upholstered furniture, fixing of leather, foil, paper, cardboard, roller-binds, awnings, packagings

Length: 221 mm
 Width: 43 mm
 Height: 144 mm

Technical data

Type description:	95/16-425 Standard	95/16-425 Contact
Article code:	12000071	12000072
Magazine type :	Bottom loader	Bottom loader
Safety:	-	Contact actuation
Fastener type:	Type 95	Type 95
Magazine capacity:	114	114
Fasteners per strip:	1 x 100	1 x 100
Operating pressure:	5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar	6 bar
Air consumption/operation:	0,3 litre / 6 bar	0,3 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB	L WA, 1 s,d= 87 dB
Weight:	0.95 kg	0.95 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description
14400827	Adjustable roller edge guide (assembly in factory)
14400838	Adjustable roller edge guide (assembly in factory)
14400862	Roller edge guide, resilient (assembly in factory)
14400679	Back nose assembly 3 mm. Please note on orders.
14406023	Back nose assembly 6 mm. Please note on orders.
14403330	Remote valve, compl.

All BeA pneumatic tools can be jig-mounted
 We supply the necessary accessories and equipments.




This tool conforms to the EG Directive for Machinery (89/392 EWG)

Pneumatic Tacker Type 95/16-425

Staples type 95



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
95/04 NK	4
95/06 NK	6
95/08 NK	8
95/10 NK	10
95/12 NK	12
95/14 NK	14
95/16 NK	16

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut