

## Pneumatic Pinner Type S 717-410

A lightweight pinner for small pins type S 700 with 0,7 mm in diameter. The pinner drives fasteners in the range from 10 to 17mm. For use of pins 14 and 17mm's only, the installation of the feeder bar no. 14401372 is recommended.

The S 700 pins are perfect for attaching delicate moldings and trim to all kinds of furniture, store fixtures and decorative accessories. The driven pin is virtually undetectable



### Popular applications:

Furniture molding and decorative trim.

Length: 225 mm  
Width: 40 mm  
Height: 149 mm

### Technical data

Type description:	<b>S 717-410 Standard</b>
Article code:	12000052
Magazine type :	Side loader
Safety:	-
Fastener type:	Pins type S 700
Magazine capacity:	160
Fasteners per strip:	2 x 80
Operating pressure:	5 – 6 bar
Max. operating pressure:	6 bar
Air consumption/operation:	0.3 litre / 6 bar
Inner hose diameter:	Ø 6 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 82 dB
Single-shot sound pressure level:	L WA, 1 s, d= 87 dB
Weight:	1.01 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.  
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

### Accessories:

Articel code	Description
14400590	Screw cap with eye hook
14401372	Feeder bar
14403330	Remote valve compl.
14403535	Mounting flange
14400674	Screw cap, Alu

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)


## Pneumatic Pinner Type S 717-410

### Pins type S 700



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: +49 (0) 4102 78-0  
Fax: +49 (0) 4102 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG



Description	L = Length mm
S 710 NK	10
S 712 NK	12
S 714 NK	14
S 717 NK	17

Other lengths and finishes are also available on request.

#### Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut